



# Topcon Receiver Utility (TRU)

---

## Release Notes

**Version 3.6**

**June 2021**

©Copyright Topcon Positioning Systems, Inc. 2021.

All contents in this manual are copyrighted by Topcon. All rights reserved. The information contained herein may not be used, accessed, copied, stored, displayed, sold, modified, published, or distributed, or otherwise reproduced without express written consent from Topcon.

## Table of Contents

<b>VERSION 3.6 .....</b>	<b>3</b>
<b>FEATURES AND CHANGES .....</b>	<b>3</b>

## Version 3.6

(Release build number r169638)

### *Features and Changes*

- GNSS FW 5.4 support
- Added limited compatibility with Wine
- Added support for Topnet Live Starpoint and Skybridge services
- Windows Mobile / Windows CE support improved
- MC GX-55 and GX-60 support improved
- Predefined message sets updated
- Support of V5 message added
- Support basic PPP settings
- New representation of PPP-related options added (VPPP, SPPP, CRYP)
- Boot section hash displayed
- Added inter-antenna distance, RMS for heading and inclination to the Attitude tab.
- AMP setting added
- GPS L1C signal supported
- Spoofing detector GUI added
- Support RINEX 3.04
- Support NavIC in positioning
- Serial update via BLE for GCX3
- Export/Import AdvComm parameters
- Expired OAF can be updated
- Added support for TILT and METEO sensors.
- Redesigned File Explorer.
- Added support for storage quotas in the file system.
- Enhanced support for storage devices.
- Added ability to select storage device.
- Added support for GR-i3F firmware update.
- Added support for tracking SBAS L5 signal.
- Added support for tracking QZSS L6 signal.
- Renamed Variable RTK to Spectrum RTK.
- Added support for satellite navigation codes 21 and 46.
- Added representation of options for Topnet Live and spoofing detector.
- Updated signal names for BeiDou Phase 2 and 3 satellites.
- Added antenna DC status on the Misc tab.